


Environmental Protection Report

River Sid Catchment River Water Quality Classification 1991

April 1992 WQP/92/005 Author: B L Milford Water Quality Planner



C V M Davies Environmental Protection Manager

ACKNOWLEDGEMENTS

The Water Quality Planner acknowledges the substantial contributions made by the following staff:

R Broome - Co-ordinator and Editor Freshwater Planning - Production of Maps C McCarthy - Administration and report compilation A Gurney - Statistical Schedule production

Thanks are extended to A. Burghes of Moonsoft, Exeter for computer support.

Suggestions for improvements that could be incorporated in the production of the next Classification report would be welcomed.

Further enquiries regarding the content of these reports should be addressed to:

Freshwater Officer, National Rivers Authority, Manley House, Kestrel Way, EXETER, Devon EX2 7LQ




RIVER WATER QUALITY IN THE RIVER SID CATCHMENT

i.

4

LIST OF CONTENTS

1	Introduc	ction	1
2	River S	id Catchment	1
3	National	l Water Council's River Classification System	1
4	1991 Riv	ver Water Quality Classification	2
5	Non-com	pliance with Quality Objectives	3
6	Glossar	y of Terms	4
7	Referen	ces	4
8	Appendi	ces:	
	8.1	River Quality Objectives including Monitoring points - map format	
	8.2	Basic Determinand Analytical Suite	
	8.3	National Water Council (NWC) River Classification System	
	8.4	NWC Criteria for Non-Metallic Determinands - Regional Variation	
	8.4.1	NWC Criteria for Metallic Determinands - Regional Variation	
	8.5	1991 River Water Quality Classification - tabular format	
	8.6	1991 River Water Quality Classification - map format	
	8.7	Calculated Determinand Statistics used for Quality Assessment - tabular format	
	8.8	Compliant/Non-Compliant River Reaches - map format	
	8.9	Number of Samples Results exceeding quality standards - tabular format	
	8.10	Percentage Exceedance of Determinand Statistics from Quality Standard - tabular format	



1. INTRODUCTION

Monitoring to assess the quality of river waters is undertaken in thirty-four catchments within the region. As part of this monitoring programme samples are collected routinely from selected monitoring points at a pre-determined frequency per year, usually twelve spaced at monthly intervals. Each monitoring point provides data for the water quality of a river reach (in kilometres) upstream of the monitoring point.

Each water sample collected from each monitoring point is analysed for a range of chemical and physical constituents or properties known as determinands. The analytical results for each sample are entered into a computer database called the Water Quality Archive.

Selected data are accessed from the Archive so that the quality of each river reach can be determined based on a River Classification System developed by the National Water Council (NWC), (7.1).

This report presents the river water quality classification for 1991 for monitored river reaches in the River Sid catchment.

2. RIVER SID CATCHMENT

The River Sid flows over a distance of 10.2 km from its source to the tidal limit, (Appendix 8.1). Water quality was monitored at three sites at approximately monthly intervals.

Throughout the Sid catchment one secondary tributary of the River Sid was monitored.

2.1 SECONDARY TRIBUTARY

The Roncombe Stream flows over a distance of 4.5 km from its source to the confluence with the River Sid, (Appendix 8.1) and was monitored at approximately monthly intervals.

Each sample was analysed for a minimum number of determinands (Appendix 8.2) plus additional determinands based on local knowledge of the catchment. In addition, at selected sites, certain metal analyses were carried out.

The analytical results from all of these samples have been entered into the Water Quality Archive and can be accessed through the Water Resources Act Register, (7.2).

3. NATIONAL WATER COUNCIL'S RIVER CLASSIFICATION SYSTEM

3.1 River Quality Objectives

In 1978 River Quality Objectives (RQOs) were assigned to all river lengths that were part of the routine monitoring network and to those additional watercourses, which were not part of the routine network, but which received discharges of effluents. For the majority of watercourses long term objectives were identified based on existing and assumed adequate quality for the long term protection of the watercourse. In a few instances short term objectives were identified but no timetable for the achievement of the associated long term objective was set.

The RQOs currently in use in the River Sid catchment are identified in Appendix 8.1.

3.2 River Quality Classification

River water quality is classified using the National Water Council's (NWC) River Classification System (see Appendix 8.3), which identifies river water quality as being one of five quality classes as shown in Table 1 below:

Table 1 - National Water Council - River Classification System

<u>Class</u>	Description
1A	Good quality
1B	Lesser good quality
2	Fair quality
3	Poor quality
4	Bad quality

Using the NWC system, the classification of river water quality is based on the values of certain determinands as arithmetic means or as 95 percentiles (5 percentiles are used for pH and dissolved oxygen) as indicated in Appendices 8.4 and 8.4.1.

The quality classification system incorporates some of the European Inland Fisheries Advisory Commission (EIFAC) criteria (Appendix 8.3) recommended for use by the NWC system.

4. 1991 RIVER WATER QUALITY CLASSIFICATION

Analytical data collected from monitoring during 1989, 1990 and 1991 were processed through a computerised river water quality classification programme. This resulted in a quality class being assigned to each monitored river reach as indicated in Appendix 8.5.

The quality class for 1991 can be compared against the appropriate River Quality Objective and previous annual quality classes (1985-1990) also based on three years combined data, for each river reach in Appendix 8.5.

The river water classification system used to classify each river length is identical to the system used both in 1985 and 1990 for the Department of the Environment's Quinquennial River Quality Surveys. The determinand classification criteria used to determine the annual quality classes in 1985, subsequent years and for 1991 are indicated in Appendices 8.4 and 8.4.1. The river quality classes for 1991 of monitored river reaches in the catchment are shown in map form in Appendix 8.6.

The calculated determinand statistics for pH, temperature, dissolved oxygen, biochemical oxygen demand (BOD), total ammonia, un-ionised ammonia, suspended solids, copper and zinc from which the quality class was determined for each river reach, are indicated in Appendix 8.7.

5. NON-COMPLIANCE WITH QUALITY OBJECTIVES

Those monitored river reaches within the catchment, which do not comply with their assigned (RQO), are shown in map form in Appendix 8.8.

Appendix 8.9 indicates the number of samples analysed for each determinand over the period 1989 to 1991 and the number of sample results per determinand, which exceed the determinand quality standard.

For those non-compliant river reaches in the catchment, the extent of exceedance of the calculated determinand statistic with the relevant quality standard (represented as a percentage), is indicated in Appendix 8.10.

6. GLOSSARY OF TERMS

RIVER REACH

RIVER LENGTH

RIVER QUALITY OBJECTIVE

95 percentiles

5 percentiles

BIOLOGICAL OXYGEN DEMAND (5 day carbonaceous ATU)

pН

UN-IONISED AMMONIA

SUSPENDED SOLIDS

USER REFERENCE NUMBER

INFERRED STRETCH

A segment of water, upstream from sampling point to the next sampling point.

River distance in kilometres.

That NWC class, which protects the most sensitive use of the water.

Maximum limits, which must be met for at least 95% of the time.

Minimum limits, which must be met for at least 95% of the time.

A standard test measuring the microbial uptake of oxygen - an estimate of organic pollution.

A scale of acid to alkali.

Fraction of ammonia poisonous to fish, NH³.

Solids removed by filtration or centrifuge under specific conditions.

Reference number allocated to a sampling point.


Segment of water, which is not monitored and whose water quality classification is assigned from the monitored reach upstream.

7. REFERENCES

Reference

- 7.1 National Water Council (1977). River Water Quality: The Next Stage. Review of Discharge Consent Conditions. London.
- 7.2 Water Resources Act 1991 Section 190.
- 7.3 Alabaster J. S. and Lloyd R. Water Quality Criteria for Freshwater Fish, 2nd edition, 1982. Butterworths.

4



BASIC DETERMINAND ANALYTICAL SUITE FOR ALL CLASSIFIED RIVER SITES

pH as pH Units Conductivity at 20 C as uS/cm Water temperature (Cel) Oxygen dissolved % saturation Oxygen dissolved as mq/1 OBiochemical oxygen demand (5 day total ATU) as mg/1 O Total organic carbon as mg/l C Nitrogen ammoniacal as mg/l N Ammonia un-ionised as mg/1 N Nitrate as mg/l N Nitrite as mg/l N Suspended solids at 105 C as mg/l Total hardness as mg/l CaCO3 Chloride as mg/l Cl Orthophosphate (total) as mg/1 PSilicate reactive dissolved as mg/l SiO2 Sulphate (dissolved) as mg/1 SO4 Sodium (total) as mg/l Na Potassium (total) as mg/l K Magnesium (total) as mg/1 Mg Calcium (total) as mg/l Ca Alkalinity as pH 4.5 as mg/l CaCO3

		NWC RIVE	R QUALITY	CLASSIFICATION SYSTEM		
River Class		Quality criteria		Remarks	Curren	et potential uses
		Class limiting criteria (95 percenti	ile)			1
1A Good Quality	(i) (ii) (iii) (iv) (v)	Dissolved oxygen saturation greater than 80% Biochemical oxygen demand not greater than 3 mg/l Ammonia not greater than 0.4 mg/l Where the water is abstracted for drinking water, it complies with requirements for A2* water Non-toxic to fish in EIFAC terms (or best estimates if EIFAC figures not available)	(ii)	Average BOD probably not greater than 1.5 mg/l Visible evidence of pollution should be absent	(i) (ii) (iii)	Water of high quality suitable for potable supply abstractions and for all abstractions Game or other high class fisheries High amenity value
19 Good Quality	(i) (ii) (iii) (iv) (v)	DO greater than 60% saturation BOD not greater than 5 mg/1 Ammonia not greater than 0.9 mg/1 Where water is abstracted for drinking water, it complies with the requirements for A2* water Non-toxic to fish in EIFAC terms {or best estimates if EIFAC figures not available}	(i) (ii) (iii) (iv)	Average BOD probably not greater than 2 mg/l Average ammonia probably not greater than 0.5 mg/l Visible evidence of pollution should be absent Waters of high quality which cannot be placed in Class 1A because of the high proportion of high quality effluent present or because of the effect of physical factors such as canalisation, low gradient or eutrophication Class 1A and Class 1B together are essentially the Class 1 of t River Pollution Survey (RPS)		Water of less high quality than Class 1A but usable for substantially the same purposes
2 Fair Quality	(i) (ii) (iii) (iv)	DO greater than 40% saturation BOD not greater than 9 mg/l Where water is abstracted for drinking water it complies with the requirements for A3* water Non-toxic to fish in EIFAC terms (or best estimates if EIFAC figures not available)	(i) (ii) (iii)	Average BOD probably not greater than 5 mg/l Similar to Class 2 of RPS Water not showing physical signs of pollution other than humic colouration and a little foaming below weirs	(i) (ii) (iii)	Waters suitable for potable supply after advanced treatwent Supporting reasonably good coarse fisheries Moderate amenity value

.

....

APPENDIX &

9 Poor Quality	(i) (ii) (iii)	DO greater than 10% saturation Not likely to be anaerobic BOD not greater than 17 mg/l. This may not apply if there is a high degree of re-aeration	Similar to Class 3 of RPS	Naters which are polluted to an extent that fish are absent only sporadically present. May be used for low grade industrial abstraction purposes. Considerable potential for further use if cleaned up
4 Bad Quality		Waters which are inferior to Class 3 in terms of dissolved oxygen and likely to be anaerobic at times	Similar to Class 4 of RPS	Waters which are grossly polluted and are likely to cause nuisance
L I		BO greater than 10% saturation		Insignificant watercourses and ditches not usable, where the objective is simply to prevent nuisance developing
.				

- Notes (a) Under extreme weather conditions (eg flood, drought, freeze-up), or when dominated by plant growth, or by aquatic plant decay, rivers usually in Class 1, 2, and 3 may have BODs and dissolved oxygen levels, or ammonia content outside the stated levels for those Classes. When this occurs the cause should be stated along with analytical results.
 - (b) The BOB determinations refer to 5 day carbonaceous BOD (ATU). Ammonia figures are expressed as WH+. **
 - (c) In most instances the chemical classification given above will be suitable. However, the basis of the classification is restricted to a finite number of chemical determinands and there may be a few cases where the presence of a chemical substance other than those used in the classification markedly reduces the quality of the water. In such cases, the quality classification of the water should be down-graded on the basis of biota actually present, and the reasons stated.
 (d) EIFAC (European Inland Fisheries Advisory Commission) limits should be expressed as 95 percentile limits.

EEC category A2 and A3 requirements are those specified in the EEC Council directive of 16 June 1975 concerning the Quality of Surface. Water intended for Abstraction of Drinking Water in the Nember State.

Ammonia Conversion Factors

 $(mg NH_4/1 \text{ to } mg N/1)$

Class	18	0.4	ng	NH4/1	:	0.31	mş	N/1
Class	18	0.9	ng	NH4/3	:	0.70	ng	N/1
		0.5	ng	NH4/1	:	0.39	ng	N/1

APPENDIX 8.4

NWC RIVER CLASSIFICATION SYSTEM

CRITERIA USED BY NATIONAL RIVERS AUTHORITY - SOUTH WEST REGION FOR NON-METALLIC DETERMINANDS

- River Quality Criteria Class
- 1A Dissolved oxygen % saturation greater than 80% BOD (ATU) not greater than 3 mg/l O Total ammonia not greater than 0.31 mg/l N Non-ionised ammonia not greater than 0.021 mg/l N Temperature not greater than 21.5 C pH greater than 5.0 and less than 9.0 Suspended solids not greater than 25 mg/l
- 1B Dissolved oxygen % saturation greater than 60% BOD (ATU) not greater than 5 mg/1 O Total ammonia not greater than 0.70 mg/1 N Non-ionised ammonia not greater than 0.021 mg/1 N Temperature not greater than 21.5 C pH greater than 5.0 and less than 9.0 Suspended solids not greater than 25 mg/1
 - 2 Dissolved oxygen & saturation greater than 40% BOD (ATU) not greater than 9 mg/1 O Total ammonia not greater than 1.56 mg/1 N Non-ionised ammonia not greater than 0.021 mg/1 N Temperature not greater than 28 C pH greater than 5.0 and less than 9.0 Suspended solids not greater than 25 mg/1
 - 3 Dissolved oxygen % saturation greater than 10% BOD (ATU) not greater than 17 mg/l O
 - 4 Dissolved oxygen % saturation not greater than 10% BOD (ATU) greater than 17 mg/l 0

STATISTICS USED BY NATIONAL RIVERS AUTHORITY - SOUTH WEST REGION

Statistic

Dissolved oxygen BOD (ATU) Total ammonia Non-ionised ammonia Temperature pH

Determinand

Suspended solids

5 percentile 95 percentile 95 percentile 95 percentile 95 percentile 95 percentile 95 percentile arithmetic mean

NWC RIVER CLASSIFICATION SYSTEM

CRITERIA USED BY NATIONAL RIVERS ALTHORITY - SOUTH WEST REGION FOR METALLIC DETERMINANDS

SOLUBLE COPPER

Total Hardness (mean) mg/l CaCO3	Statistic	Soluble Copper* ug/l Cu Class l Class 2
$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	95 percentile 95 percentile 95 percentile 95 percentile	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$

.

. .

Total copper is used for classification until sufficient data on soluble copper can be obtained.


TOTAL ZINC

Total Hardness (mean) mg/l CaCO3	Statistic	Total Zinc ug/l Zn Class 1 Class 2 Class 3
$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	95 percentile 95 percentile 95 percentile 95 percentile	<pre>< = 30 < = 300 > 300 < = 200 < = 700 > 700 < = 300 < = 1000 > 1000 < = 500 < = 2000 > 2000</pre>

NATIONAL RIVERS AUTHORITY - SOUTH WEST REGION 1991 RIVER WATER QUALITY CLASSIFICATION CATCHMENT: SID

.

1991 Map	River	Reach upstream of	User	National	Reach	Distance	River	85	86	87	88	89	(90	1 91
Position	1		Reference	Grid	Length	from	Quality	NWC	NWC	NWC	NWC	NWC	NWC	NWC
Number	Ì		Number	Reference	(km)	source	Objective	Class	(Class	Class	Class	Class	Class	Class
1	Ì	1	1	1	1	((km)	1	1	1	1	1 1	1	ł	1
Í	1	1	1	1		I			1	l -	[1	1
i	j	1	ł			1	9	I	1	1		1	1	1
i	ĺ	1	Ì	İ _	l	·	Í!		I	I	i I	l	[1
1 1	SID	STONEY BRIDGE SIDBURY	R03A001	SY 1400 9165	5.0	5.0	<u> </u>	2	3	2	18	1.	18	1B
1 2	SID	A3052 BRIDGE SIDFORD	R03A002	SY 1375 8995	1.8	6.8	1A	1A	j 3	2 -	2	1 1 A	18	18
j 3	SID	SIDMOUTH	R03A003	SY 1280 8780	2.9	9.7	1A	1A	3	2	2	11	1B	18
i	SID	NORMAL TIDAL LIMIT (INFERRED STRETCH)	1	Í	0.5	10.2	1A	1A	3	2	2	1A	(1B	[1B
i	i	İ	ĺ				L	I	l	[i			l	I
1 4	RONCOMBE STREAM	COTFORD	R03A013	SY 1423 9222	4.4	4.4	1A	I	1	1			2	13
i	RONCOMBE STREAM	NORMAL TIDAL LIMIT (INPERRED STRETCH)	1		0.1	4.5	j 1A		1	I	I		2	3
i .	i	İ	l!	l		li	1	!	I		II	I	I	I




NRCICINAL RIVERS AUGURETY — SOUTH WEST REFERN 1991 RIVER WRIER QUALITY CLASSIFICATION CALCULATED DETERMINING STRUISTICS USED FOR QUALITY ASSESSMENT CRICHMENT: SID

1

River	Reach upstream of	User	ROD			Calcul	sted Det	nenirat	d Statis	tics us	ad for Q	unlity	Assesses	nt.									
1		Ref.				1		1		I		1				1		1		1		1	1
1	3	Number		pH I	CHER	p≞ti	ipper	Temp	erature	1 00	(\$)	BCI	d (MTU)	Total	Amenia	(Uhion	. Amonia	S.S	blids	Total	Capper	Tota	l Zinc
1	r.	ŧ.		Class	5kile	Class	95kile	Class	95kile	Class	Stile	عمل إ	s 95kile	Class	i 95kilo	عمل إ	s 95%ile	Class	s Meen	Class	95kile	Case) ملك39 ا
1	1	1				ŧ		1		ļ –		l i		I		I		1		I I		1	1
	1	1				1				l –		1		1		1		1		1		1	1
ll		<u> </u>	L			l		I		<u> </u>		l		<u> </u>		L				<u> </u>			
SID	STONEY BRIDGE STIBLIRY	F03A001	118	1A	7.3	11	0.3	1A	16.8	1 118	80.0	118	3.3	17	0.124	<u>1</u>	0.010	14	6.8	-	-	- 1	-
SID	A3052 BRIDGE SILFORD	R03A002	1A	1A	7.4	1 IA	8.5	AL	18.0	AL	85.0	18	3.7	11	0.120	1A	0.010	AL	8.2	-	- /	-	- (
SID	SIDMOUTH	R034003	1A	1A	7.7	14	8.7	1A	18.1	1A	88.0	1B	3.5	1A	0.133	I IA	0.010	14	7.9	1A	12.2	14	13.1
]I	1	11						l		I		l				L		l		<u> </u>		<u> </u>	
RONCOMBE STREAM	COLLACED	1032013	IA	AL	7.3	AL	8.5	17	17.0	AL	83.8	3	9.4	I JA	0.143	1A	0.010	1	10.9	1 17	10.0	2	608.6
1	1	<u> </u>	l			I		I		<u> </u>		<u> </u>		<u> </u>		l				1		L	

- -



NATIONAL RIVERS AND RITY - SOUTH WEST REGION 1991 RIVER WHER QUALITY CLASSIFICATION NUMBER OF SAMPLES (N) AND NUMBER OF SAMPLES EXCEPTIONS QUALITY STANDARD (F) CHICHMENT: SID

River	Reach upstream of	User	pH Lo	MBC	वस	tper	Tempera	enute		(*)	BOD	ATU)	Total A	munia	júnian.	Annonia	S.So	lids	Total	Opper	Total	Zinc
1, 1	*	Ref.			ł		1		1		1		1						l	l		
		Ninber	N	r	N	F	t N	F	1 11	F	N	P	114	F	N	F	19	F	14	F	2	P [
- Q	1				1		1				I		ł		1		1		l			1
Ц	1.14	I I			1		1				l						1		1			1
1		1 1			1		1		1		l i		1									
<u> </u>					<u> </u>		l		Į		I	_	<u> </u>		L							
••	STONEY BRIDGE SIDELRY	P034001		-	30	-	29	-	29	-	30	-	30	-	27	-	30	-	1	-	1	
SID	A3052 BRIDE SILFURD	R03A002	34	-	34	-	32	-	32	-	34	2	34	-	29	-	34	1	2	- 1	2	- 1
ISTD	SUMOUTH	[R034003]	37	-	37	-	37	-	37	-	37	2	37	-	32	-	37	1	37	-	37	-
11				_	l		<u> </u>					_	<u> </u>				l		L			
RONCIME STREAM	COLFORD	R03A013	33	-	33	-	33	_	33	-	33	-3	33	_	30	-	33	3	20	- (20	1
11					1		1		[1		l							

NATIONAL RIVERS AUTHORITY - SOUTH WEST REGION 1991 RIVER WATER QUALITY CLASSIFICATION PERCENTAGE EXCEEDENCE OF DETERMINAND STATISTICS FROM QUALITY STANDARDS CATCHMENT: SID

River	Reach upstream of	User		PERCENTAGE	EXCEEDENCE OF	STATISTIC	FROM QUALIT	Y STANDARD				
]1		Ref.		l	1		I I		1	1 1	1)
] ['	Number	pH Lower	pH Upper	Temperature	DO (%)	BOD (ATU)	Total	Un-ionised	Suspended:	Total	Total
4 I		1						Ammonia	Ammonia	Solids	Copper	Zinc
11	1.	1 1		ł	1		1 1		1	1 1	1	
] [-		1 1		ļ — — — — — — — — — — — — — — — — — — —	1		1 1		1			
1		_II	a la companya da companya da companya da companya da companya da companya da companya da companya da companya d	1	I		ll			II		
SID	STONEY BRIDGE SIDBURY	R03A001		-	-	-	- 1	-	-	-	-	
SID	A3052 BRIDGE SIDFORD	R03A002	10 0 0	-	-	-	22	-	-	-	-	-
SID	SIDMOUTH	R03A003	11 -1 11-1	-	-	-	16	-		- 1	-	- 1
li	j_i	1_ i					11		1	اا		
RONCOMBE STREAM	COTFORD	R03A013	10÷0	-	-		213	-			<u> </u>	22 .
11		1			-		II		1	I		!